



Approximately 46" x 51"

Quilt designed by Donna Russell

Please read through all of the instructions before you begin your project.

Fabric Requirements:

- A. Pattern #24876-Mul1.....1 panel
 B. Pattern #24878-Mul1.....3/4 yard*
 C. Pattern #24879-Mul1.....3/8 yard
 D. Pattern #24882-Oli1.....3/4 yard
 E. Pattern #24881-Oli1.....2-3/8 yards
 Batting.....1 piece 52" x 57"

* See cutting instructions and illustrations.

Cutting Instructions:

Please read all instructions carefully before beginning. All seams are a scant 1/4" which is included in all measurements unless otherwise stated. Cut pieces in order listed. Label all pieces. Refer to all illustrations and the quilt image for proper cutting and assembly.

** wof = width of fabric, lof = length of fabric.*

Fabric A - Owls Panel (24876-Mul1)

1. Fussy cut panel 21-1/2" x 42-1/2" .
Label: "C".

Fabric B – Owls Shelf (24878-Mul1)

1. Fussy cut (1) 8-1/2" x 42-1/2" strip.
Begin cutting at the top of the brown wooden stripe above the owls in the barn and ending below the wooden stripe beneath the owls in the green stripe. Label: B".



2. Fussy cut (1) 8-1/2" x 42-1/2" strip, this time begin cutting at the top of the wooden stripe above the owls in the green stripe and ending below the brown wooden stripe beneath the owls in the barn. Label: "D".



Fabric C – Owls in Trees (24879-Mul1)

1. Cut (2) 5-1/2" x 42-1/2" strips. Label one of these strips "A" and one "E".

Fabric D – Foliage, olive (24882-Oli1)

1. Cut (5) 2-1/2" x wof strips. Set aside for the binding.
2. Cut (2) 2-1/2" x 42-1/2" strips.
Label: "Border, top and bottom.
3. Cut (3) 2-1/2" x wof. Set aside for the side borders.

Fabric E – Tossed Owls (24881-Oli1)

1. Cut (1) piece 54" x 42-1/2".
2. Cut (2) pieces 27-1/4" x 18".
Set these pieces aside for the backing.

Piecing Instructions:

Refer to the image of the quilt on the first page to accurately place the pieces.

1. Sew "B" to the top edge of "C".
2. Sew "D" to the bottom edge of "C".
3. Sew "A" to the top edge of "B".
4. Sew "E" to the bottom edge of "D".
5. Sew one "Border, top/bottom" to the top edge of the quilt and the other one to the bottom edge.
6. Cut one of the side border pieces in half and sew (1) of the halves to each of the remaining strips to make (2) long strips. Cut each of these strips to 51-1/2" and sew one to each side edge of the quilt.

Finishing:

1. Layer the quilt top with the batting and backing and quilt as desired.
2. Trim the backing and batting even with the quilt top.
3. Sew the binding strips end to end with a diagonal seam to form one long strip.
4. Press the strip in half, lengthwise, wrong sides together.
5. Sew to the quilt front, matching the raw edges of the binding with the edge of quilt and sew, mitering the corners.
6. Turn the binding to the back and stitch in place.
Enjoy your quilt!

**Disclaimer: Please note that the instructions for this quilt are written for the specified fabric line from SPX Fabrics. If substitutions of fabric other than those stated in the instructions are used, the pattern may not yield the desired results, and the actual yardages may vary.*